

Grauwasser Recycling System, 250 l/d

Greywater Recycling System, 250 l/d

GWI 1.0-250, indoor

GreenLife

Technisches Datenblatt / technical data

Kapazität		capacity
Gesamtvolumen Stufe 1		500 l
Gesamtvolumen Stufe 2		500 l
Tagesfiltrationsleistung		250 l
DEA Klarwasserdruckpumpe X1000		
max. Förderstrom Betriebswasser		5,4 m³/h
max. Betriebsdruck Betriebswasser		3,6 bar
Motorleistung		900 W
Anschlüsse		connections
Trinkwasser-Nachspeisung		potable water back-up
Betriebswasser		service water
Zulauf in die Anlage		input to unit
Überlauf in Kanalisation		overflow to sewage
Aufstellraum muss ausreichend belüftet und mit Bodenablauf versehen sein.		Working room needs to be airventilated, floor drain necessary.
Steuerung		control unit
Zeitintervalle für Belebung, Filtration vorprogrammiert*		time interval for aeration, filtration pre-programmed*
Abmessungen (B x H x T)		measurements (W x H x D)
* Anpassung bedarfsseitig möglich		* possible adjustment according demand
Trinkwasser-Nachspeisung		mains water back-up
Magnetallaufventil (optional, größer möglich)		DN 13
Netzanschluss		electric main supply
Spannung		230 V / 50 Hz
Absicherung		bauseitig / by customer
Gewicht, Maße, Farbe		weight, measurements, colour
Leergewicht, Anlage		110 kg
max. Gesamtgewicht im Betrieb		1.150 kg
Tank Filtration		Ø 640, H 1.650 mm
Farbe		lichtgrau / light grey
Volumen		1x 500 l
Zulauf Grauwasser		1.470 mm
Zulauf Belebung		1.360 mm
Überlauf Grauwasser		1.470 mm
Tank Servicewasser		Ø 640, H 1.650 mm
Farbe		lichtgrau / light grey
Volumen		1x 500 l
Trinkwasser-Nachspeisung		1.500 mm
Entleerung		100 mm
Trinkwassernachspeisung		drinking water feed
Betriebswasseranschluss		service water connection

Grauwasser Recycling System, 250 l/d

Greywater Recycling System, 250 l/d

GWI 1.0-250, indoor

GreenLife

The **GreenLife greywater-recycling-system GWI 1.0-250** has a daily greywater filtration capacity of up to 250 liters.

The **greywater-recycling-systems of GreenLife** are configured for the treatment of greywater, i.e. low polluted waste water from personal hygiene (shower, bath tub, hand washbasin). The applied BioMembranefilter-technology assures the complete separation of the biomass from the cleaned greywater. The clearwater is free from solids and a complete blocking of bacteria and germs, with a blocking rate of 99,9999%, guaranteed. The total recycling process is composed of the biological treatment, the ultrafiltration (MBR-Membrane bio-reactor) and will be stored after it in the clearwater tank.

The result is clear germ free service water (non-potable) available for reuse in WC's, cleaning purposes, garden irrigation and/or industrial applications!

results:

The quality of the service water (non-potable) fulfills the requirements of the European (EU) guidelines for bathing water 76/160/EEC and 2006/7/EC and DIN 19650, class 2.

consisting of:

- 1 filtration tank** incl.:
greywater inflow, membrane filter and filtrate box, filtrate pump, negative buoyancy, cable and hose bushings,
- 2 service water tank** incl.:
filtrate access, connection drinking water feed unit (optional), connection twin pump station (optional)
- 3 control unit** incl.:
stainless steel bracket, aeration pump, control module, cable and connecting plug (completely programmed and pre-assembled),



www.greenlife.de